



TECHNICAL CHARACTERISTICS

- 1) CURRENT RATING : 40 AMPS. AT 415 V.A.C.
- 2) NO. OF. CONTACTS : 2 (1NO.+ 1NC. OR 2NC.)
- 3) MODE. OF OPERATION : 1 WAY, SELF RE-SETTING
- 4) MAX. SWITCHING FREQUENCY : 720 PER HR.
- 5) DESIGN CONFIRMS TO IS/IEC 60079 - 1:2007, IS/IEC 60079-0:2011 FOR GAS GROUP IIC IN ALLOY LM-6 GRADE CONSTRUCTION, IP:66 AS PER IS/IEC:60529-2001 & DUST IGNITION PROTECTION AS PER IS/IEC: 60079-31:2008.

Suni® Cranes Controls AN ISO 9001:2015 CERTIFIED COMPANY		सनी क्रेन्स कन्ट्रोलस एन आय.एस.ओ.९००१:२०१५ सर्टीफाईड कम्पनी		
Shubh Indl. Estate Vasai(E) PALGHAR-401208				
ALL DIMENSIONS ARE IN MM.		TOL — OVERALL DIM ±5MM. BOLTING CENTER ±3MM.		
TITLE. FLP/WP GRAVITY LIMIT SWITCH				
DRN.	PRAKASH	27/03/16	SCALE	N.T.S.
CHD.	G.G.YADAV	27/03/16	MATL.	AS ABOVE
APPD.	G.G.YADAV	27/03/16	TYPE NO. Suni/FCWLSISE2	
DRG. NO.	Suni/ GA / CWLS/02C			REV -0

CIMFR CRT.No	CIMFR/TC/P/357	DATE:-27.04.17
CCE No.	A/P/HQ/MH/104/6044 (P411322/2)	
BIS No.	CM /L 7800028013 DATED 27-09-2017	